MT-4612

Temperature Range	50°C~580°C(-58°F ~1076°F)
Accuracy	±2°C or ±2%°C
Distance Spot Ratio	16∶1
Emissivity	0.1~1.0
Laser class	Class II , <1mW
Response time & Wavelength	500ms / 8-14μm
Repeatability	±1°C or ±1%°C
Resolution	0.1°C
Unit selection	°C /°F
Data memory	9 memories
Laser target point	Dual Laser / can be selected on / off
Storage temperature	-20-50°C (-4-122°F)
Operating temperature	0~50°C, 10~95%RH
Power source	6F22(9V) (not included)
Certificate	CE, RoHS, FCC, FDA
Dimension	175*130*45mm
Weight	204g (not including battery)

8PK-ST850

- Two functions in one unit including open phase and phase sequence.
- Large size alligator clips : able to clip on switch-board terminals easily.
- Identify 3 phase sequence and open phase check.
- Ideal for installing conveyor lines, pump system amd in terconnected drivers.
- No exposed metal parts. Safety features are incorporated throughout, including the push button switch designed to minimize damage due to negligence.
- Safety approval : CE marks, IEN 1010 CAT II.
- Voltage ranges: 90V~600V AC.
- Frequency Response: 59 / 60Hz.
- Size: 134x85x45 mm
- Cord: 1.1 m each of Red(R), White(S) and Black(T) cord.