



Different type of wiring connectors are available for different electrical installations.

RIPE - Hong Kong ripe

Ordering Information

Order No	Model No	Product	Nos of rows	Holes Sizes mm
208 780	VC - 207	Modular Distribution Blocks	2rows	2xØ7.5
208 782	VC - 211	Modular Distribution Blocks	2rows	2xØ7.5
208 785	VC - 215	Modular Distribution Blocks	2rows	2xØ7.5, 2xØ9.0
208 788	VC - 407	Modular Distribution Blocks	4rows	5xØ5.3
208 790	VC - 411	Modular Distribution Blocks	4rows	7xØ5.3
208 764	VC - 415	Modular Distribution Blocks	4rows	2xØ7.5

Technical Details

Connection with or without ferrules

- Supplied with insulated back plate and transparent protective front cover, self-extinguishing
- Mounting methods:
 1. Fix on din-rail
 2. On plate with 2 screws
- When installing under a front plate, a blanking plate can be clipped onto the front plate
- Insulation protection each bar
- Each bar can be labelled using cab 3TM
- Conform to standard EN60947-1
- ICC:20kA peak

Ordering Information

Order No	Model No	Product	Current	Cable Size	Size
224 820	TC-602	Terminal Block	14	60	600
224 821	TC-603	Terminal Block	14	60	600
224 822	TC-604	Terminal Block	14	60	600
224 823	TC-1002	Terminal Block	22	100	600
224 824	TC-1003	Terminal Block	22	100	600
224 825	TC-1004	Terminal Block	22	100	600
224 841	TB-1504	Terminal Block	0.5 - 1.5	15	600
224 851	TB -2512	Terminal Block	0.5 - 2.5	25	600
224 856	TB-4512	Terminal Block	0.5 - 4	45	600

Technical Details

Item No.	Rated current / Voltage	Wire range
TC - 602	60A/600V	14mm ²
TC - 603	60A/600V	14mm ²
TC - 604	60A/600V	14mm ²
TC - 1002	100A/600V	22mm ²
TC - 1003	100A/600V	22mm ²
TC - 1004	100A/600V	22mm ²
TB - 1504	15A/600V	0.5-1.5mm ²
TB - 2512	25A/600V	0.5-2.5mm ²
TB - 4512	45A/600V	0.5-4mm ²



TC - 602



TC - 1003



TB - 4512



TB - 2512